



SGK-1360S SGK-1060S SGK-630S SGK-450S SGK-320S

Operating weight	1350kg	1050 kg	650 kg	450 kg	330 kg
Tool diameter	120 mm	114 mm	105 mm	85 mm	80 mm
Oil flow	150÷160 l/min.	130÷150 l/min.	110÷130 l/min.	75÷100 l/min.	45÷85 l/min.
Working pressure	130÷140 bar	110÷120 bar	110÷120 bar	105÷115 bar	95÷105 bar
Relief valve	200 bar	170 bar	170 bar	150 bar	140 bar
Max. backpressure	12 bar	12 bar	12 bar	12 bar	12 bar
Blow energy	3000 joule	2300 joule	1700 joule	1050 joule	750 joule
Required power	50 hp	38 hp	35 hp	25,5 hp	20 hp
Impact rate	600 (750)	500÷600	600÷650	650÷900	540÷1000
Carrier weight	18÷25 ton	13÷20 ton	9÷15 ton	7÷11 ton	4,5÷9 ton
Max. noise level (silenced version)	88 db-A	88 db-A	88 db-A	90 db-A	90 db-A
Inner diameter HP line	26 mm	20 mm	20 mm	20 mm	20 mm
Inner diameter LP line	38 mm	36 mm	36 mm	30 mm	30 mm